



55 mm x 100 mm x 21 mm SKF 1211 ETN9 Self Aligning Ball Bearings

Bearing No. 1211 ETN9

1211 ETN9 Bearing 2D drawings and 3D CAD models

Category	Self Aligning Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.71
EAN	7316576624490
Product Group	B00152
Mounting Method	Shaft
Enclosure	Open
Rolling Element	Ball Bearing
Cage Material	Polyamide
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 2.5 Deg High Capacity Design
Long Description	55MM Bore; Shaft Mount; 100MM Outside Diameter; 21MM Inner Race Width; 21MM Outer Race Width; Open; Polyamide Cage; Double Row of Balls; ABEC 1 ISO P0; C0-Medium
Inch - Metric	Metric
Category	Self Aligning Ball Bearings
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



Keyword String	Self Aligning
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	1211 ETN9
Weight / LBS	1.565
d	2.165 Inch 55 Millimeter
Inner Race Width	0.827 Inch 21 Millimeter
Outer Race Width	0.827 Inch 21 Millimeter
D	3.937 Inch 100 Millimeter
bore diameter:	55 mm
precision rating:	Not Rated
outside diameter:	100 mm
maximum rpm:	9000 RPM
overall width:	21 mm
cage material:	Fiberglass Reinforced Nylon
bore type:	Straight
finish/coating:	Uncoated
closure type:	Open
maximum misalignment:	2.5 °
internal clearance:	C0
outer ring width:	21 mm
dynamic load capacity:	27.6 kN
fillet radius:	1.5 mm
static load capacity:	10.6 kN
series:	1200
d	55 mm
D	100 mm
B	21 mm
d ₁	70.3 mm
D ₁	86.5 mm
r _{1,2} min.	1.5 mm
d _a min.	64 mm
D _a max.	91 mm



r_a max.	1.5 mm
Basic dynamic load rating C	27.6 kN
Basic static load rating C_0	10.6 kN
Fatigue load limit P_u	0.54 kN
Reference speed	14000 r/min
Limiting speed	9000 r/min
Permissible angular misalignment	2.5 °
Calculation factor k_r	0.04
Calculation factor e	0.19
Calculation factor Y_0	3.6
Calculation factor Y_1	3.3
Calculation factor Y_2	5.1
Mass bearing	0.71 kg