



2211 E-2RS1KTN9/C3 Bearing 2D drawings and 3D CAD models

SKF 2211 E-2RS1KTN9/C3 Self Aligning Ball Bearings

Bearing No. 2211 E-2RS1KTN9/C3

Category	Self Aligning Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.816
EAN	7316577301802
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	2 Seals
Rolling Element	Ball Bearing
Adapter Sleeve	H-311
Cage Material	Polyamide
Precision Class	ABEC 1 ISO P0
Internal Clearance	C3-Loose
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 1.5 Deg High Capacity Design 1:12 Taper
Long Description	55MM Bore; Tapered Adapter Mount; 100MM Outside Diameter; 25MM Inner Race Width; 25MM Outer Race Width; 2 Seals; Polyamide Cage; Double Row of Balls; ABEC 1 ISO P0; C3-Loose
Inch - Metric	Metric
Category	Self Aligning Ball Bearings



NTN BEARING MANUFACTURING DE MEXICO,S...

UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	2211 E-2RS1KTN9/C3
Weight / LBS	1.797
Outer Race Width	0.984 Inch 25 Millimeter
d	2.165 Inch 55 Millimeter
D	3.937 Inch 100 Millimeter
Inner Race Width	0.984 Inch 25 Millimeter
bore diameter:	55 mm
precision rating:	Not Rated
outside diameter:	100 mm
maximum rpm:	4300 RPM
overall width:	25 mm
cage material:	Fiberglass Reinforced Nylon
bore type:	Tapered 1:12
finish/coating:	Uncoated
closure type:	Double Sealed
maximum misalignment:	2.5 °
internal clearance:	C3
outer ring width:	25 mm
operating temperature range:	-40 to +210 ° F
fillet radius:	1.5 mm
dynamic load capacity:	27.6 kN
series:	2200
static load capacity:	10.6 kN